



# Multiplex Red

Multiplex Red -

Multiplex Red -

Multiplex Red

1

2

NLGI GC-LB,

- 
- 
- 
- 
- 
- 
- 
- 
- 
- 

NLGI GC-LB (

No. 1 No. 2)

**CONOCO****Multiplex Red**

NLGI	0	1	2
, °C (°F)	250 (482)	271 (520)	271 (520)
/	7.48	7.48	7.48
(60 ), ASTM D217	355-385	310-340	265-295
4-			
, ASTM D2596,	400	400	400
4-			
ASTM D2266,	<0.60	<0.60	<0.60
(			
100 ), ASTMD942	5 (35)	5 (35)	5 (35)
, ASTM D1743			
, ASTM D2509	70	70	70
4°C (40°F)	4.55	2.18	1.04
-7°C (20°F)	1.03	0.57	0.26
-18°C (0°F)	0.20	0.11	0.05
:			
cSt @ 40°C	170	170	220
cSt @ 100°C	13.8	13.8	18.0
SUS @ 100°C	905	905	1,170
SUS @ 210°F	75	75	93
	85	85	85
:			
°C	-40 194	-29 204	-23 204
°F	-40 382	-20 400	-10 400

<http://w3.conocophillips.com/NetMSDS>